MA

ज्ञापांक 704/374525 / आपूर्ति

95-1-17-2017

पुलिस महानिदेशक का कार्यालय, बिहार, पटना

पटना,दिनांक- 13·06·2018

सेवा में,

निदेशक, सूचना एवं जनसम्पर्क विभाग, बिहार, पटना

विषय- निविदा आमंत्रण सूचना सं0-02/2018-19 के प्रकाशन के संबंध में।

निदेशानुसार उपर्युक्त विषय के सबंध में निविदा आमंत्रण सूचना सं0-02/2018-19 की प्रतियाँ भेजते हुए अनुरोध है कि इसे राज्य एवं राज्य से बाहर के प्रमुख समाचार पत्रों में (अंग्रेजी एवं हिन्दी) के अगले दो संस्करणों में प्रकाशित कराने की कृपा की जाय साथ ही पी0आर0डी0 वेबसाईट पर भी प्रसारित करने की कृपा की जाय।

इस निविदा आमंत्रण सूचना का प्रकाशन किन—किन समाचार पत्रों में किया गया इसकी सूचना देने की कृपा की जाय।

अनु0—यथोपरि।

पुलिस महानिरीक्षक के सहायक (क्यू०), बिहार, पटना

प्रतिलिपि:--

- 1. आई0टी0 मैनेजर, पुलिस महानिदेशक का कार्यालय, बिहार, पटना को कृपया सूचनार्थ। कृपया इसे आज ही वेबसाइट पर अपलोड किया जाय। साथ ही Indian Trade Journal, Kolkata के अंक में प्रकाशन हेतु 'Government of India, the Controller of Publications, Civil Lines, Delhi: 110 054,(Tel No. 011-23812527, FAX: 011-23817846), Email Idsk.mondal.dgcis@nic.in के पतेपर भी अनिवार्य रूप से भेजा जाय।
- 2. Government of India, the Controller of Publications, Civil Lines, Delhi: 110 054,(Tel No. 011-23812527, FAX: 011-23817846), Email Idsk.mondal.dgcis@nic.in को कृपया सूचनार्थ एवं आवश्यक क्रियार्थ प्रेषित। अनुरोध है कि उक्त निविदा का प्रकाशन Indian Trade Journal, Kolkata के अंक में करने की कृपा की जाय।

पुलिस महानिरीक्षक के सहायक (क्यू०), बिहार, पटना

V

Police Headquarters, Bihar, Patna Notice Inviting Tender No.-02/2018-19

- 1. Name of the Department: Office of Director General of Police, Bihar, Patna.
- 2. Last date & time for the acceptance of the tender: | 6/07/2018, Till 02:00 PM
- 3. Date & time fixed for the opening of the tender: $\frac{1}{6} \frac{1}{9} \frac{1}{2018}$, At 04:00 PM
- 4. Place fixed for receiving & opening the tender: Office of Director General of Police, Bihar, Patna.
- 5. Details of Job:

S.N.	Item name	Quantity
1	Bullet Proof SUV	06

Specifications and other terms & conditions of the tender may be obtained in person from this office or may be downloaded from the website www.prdbihar.gov.in or www.biharpolice.bih.nic.in.

AIG (Q) Bihar, Patna

Terms & Conditions of Tender No.-02/2018-19




- 1. Tender of the firm will be accepted only on the condition that if their tenders are approved, the firm shall get registered with the Commercial Tax Department, Bihar, before the purchase order is issued.
- 2. The tender should be submitted in two parts: (i) Technical Bid and (ii) Financial Bid, duly sealed in two separate envelopes super-scribed as "Technical Bid" and "Financial Bid".
- 3. All relevant papers/ E.M.D./certificates/specifications etc. of items should be enclosed in the Technical Bid.
- 4. The rates of the items shall be quoted in the Financial Bid only.
- 5. All charges like IGST/CGST/SGST etc. shall be clearly included in the Financial Bid and the net rate (in figures and words) including all taxes and duties must also be quoted. Vague offers like indicating taxes "as applicable" will not be accepted.
- 6. The rates of the items shall be quoted in the Financial Bid in two parts:
 - (i) With AMC (Annual Maintenance Contract) and (ii) Without AMC
- 7. There should be no cutting, over writing or correction on the rates.
- 8. The technical and financial bids for each item should be submitted separately in separate envelopes. The technical and financial bids for more than one items submitted together in the same envelope shall not be accepted.
- 9. If the financial bid is submitted in the same envelope containing the technical bid then also it shall be summarily rejected.
- 10. The technical and financial bids should be put in two separate sealed envelopes and the envelopes should be marked Tender No-02/2018-19 (Technical Bid) and Tender No-02/2018-19 (Financial Bid) along with the name and address of the firm. The sealed envelopes containing the technical and the financial bids should be sent in another sealed envelope which should be marked as Tender No-02/2018-19. This envelope should not bear the name and address of the firm.
- 11. Income Tax Returns of last three years, a photocopy of GST registration number of the participating firm and turn-over of any two of the previous three financial years should be submitted with the technical bid. It should be specifically mentioned whether IT return has been filed manually or electronically.
- 12. The turnover of the firm for the last reported financial year should be at least equal to the amount of the supply order which is being issued. A copy of the profit and loss Account of the firm for any two of the previous three financial years, certified by a Chartered Accountant should be submitted along with the tender. If the tenderer is authorized dealer or authorized supplier of manufacturing firm, then the certified details of the turnover of authorizing firm may be accepted. Tender specific authorization from the OEM must be submitted, but in certain cases where authorization from OEM is not required, the Technical-cum-User committee (T.U.C.) shall decide about exemption (if any) on a case-by-case basis; citing appropriate reasons for the same.
- 13. If there is some discount in the price of any item, it should be deducted from price itself and such discounts should not be quoted separately.
- 14. If the product is available on DGS & D rate contract, then a copy of the contract must be attached and pricing be done including all taxes.
- 15. A copy of the test report for the product issued by any established and recognized private Laboratory or by agency accredited by the Government should be attached with the technical bid. However if required, the Technical-cum-User committee (T.U.C.) can take decision regarding exemptions/relaxations (if any), citing appropriate reasons.

4/11

- 16. In case of Bullet Proof/Bullet Resistant items, test report of TBRL or any Government Approved/Recognized Laboratory is compulsory.
- 17. Firms participating in this tender shall also submit duly sworn affidavit to the effect that " this firm has not been black listed/debarred by any Government or Semi Government or Private Agency and no sister concern of this firm is participating in this tender."
- 18. Firms participating in this tender shall also submit the self attested list of users of its equipments.
- 19. All items shall be received at Central Clothing Store, Patna; therefore price should be quoted FOR Central Clothing Store, Phulwari Sharif, Patna.
- 20. Firms will have to deposit a sum of Rs.50,000/- (Fifty Thousand) only as an earnest money deposit in the form of Bank Draft duly pledged in favor of the undersigned along with the quotations. The small scale units located in Bihar shall not be liable to deposit earnest money. Exemption from submitting E.M.D. will also be available to those who are registered with the Central Purchase Organization/State Purchase Organization and National Small Industries Corporation (NSIC).
- 21. Technical Bids will be opened on scheduled date and time in the office chamber of Police Headquarter. Representatives of the firms competing in the tender may remain present at the time of opening of the technical bid.
- 22. The technical bids will be opened first and placed before the Technical Committee of the Police Headquarters, Bihar. If the technical bids are found satisfactory as per tender conditions, it will be put before Central Purchase Committee of the Police Headquarters, Bihar. The firms may be required to participate in the demonstrations of the quoted product and discussions with this committee.
- 23. Any paper/document will not be accepted after opening the tender.
- 24. Successful firm will have to enter into an agreement after depositing a sum of 5% of the total value of the order as security money in the form of Bank Guarantee duly pledged in favor of undersigned.
- 25. The firm will be required to provide satisfactory after-sales service after the delivery of the product.
- 26. The firm will be required to supply all the items within the stipulated time frame as mentioned in the purchase order.
- 27. Payment for the delivered items will be made only after the acceptance report of the Inspection Committee of the Police Headquarters, Bihar.
- 28. The firm whose quotation is approved by the Central Purchase Committee of the Police Headquarters, Bihar, shall be invited to enter into an agreement with the undersigned.
- 29. It is expected to submit the duly filled chart attached herewith, along with the technical bid if not the tender shall be summarily rejected.
- 30. Indexing of the requisite documents must be done and submitted along with the technical bid.
- 31. Hands on training for 3 weeks of the equipment must be imparted to the user group by the firm after successful installation.
- 32. Director General of Police Bihar, Patna reserves the right to reject any or all the quotations partially or fully, without assigning any reason thereof.
- 33. The Quantity indicated may increase or decrease at the time of issuing purchase order.
- 34. The bids must be include the data sheet of individual item.

A I G (Q) Bihar, Police.





Specifications of the Bullet Proof Vehicle

Internal Fitment. Crew. Load carrying capacity Range of Operation. Speed Protection level to be provided to the vehicle	The vehicle should be a light vehicle (4x4). The additional protection material be fitted on the body as add on which do not hinder with the seating/functioning of the occupants.	
Internal Fitment. Crew. Load carrying capacity Range of Operation. Speed Protection level to be provided to the	seating/functioning of the occupants The vehicle should have adequate space for internal fitment and storage. Driver + 4 fully equipped soldiers. Note Seats to be folding type to enable carriage of stores if required. Seat belt to be catered for troops, driver and co-drivers. Minimum 500 Kgs. (a)In plains 300 to 350 kms. (b)In mountain 250 to 300 kms. (a)On Road: Not less than 80 kmph with full load. (b)X Country: Not less than 40 kmph with full load. (a)Top. With stand direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62x3 mm at a distance of 10M at an angle of 45°. (b)All Sides. With stand, direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62 x 39 mm at a distance of 10M at 90 degree angle of attack. (c)Bottom Under Carriage. Passengers / occupants should be protected against blast of hand grenade HE36 or equivalent directly under the vehicle (d)Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e)Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapne protection for fuel tank. (g) Rediator. Matching Bullet proof protection as meeticand in an article and sides.	
Crew. Load carrying capacity Range of Operation Speed Protection level to be provided to the	seating/functioning of the occupants The vehicle should have adequate space for internal fitment and storage. Driver + 4 fully equipped soldiers. Note Seats to be folding type to enable carriage of stores if required. Seat belt to be catered for troops, driver and co-drivers. Minimum 500 Kgs. (a)In plains 300 to 350 kms. (b)In mountain 250 to 300 kms. (a)On Road: Not less than 80 kmph with full load. (b)X Country: Not less than 40 kmph with full load. (a)Top. With stand direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62x3 mm at a distance of 10M at an angle of 45°. (b)All Sides. With stand, direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62 x 39 mm at a distance of 10M at 90 degree angle of attack. (c)Bottom Under Carriage. Passengers / occupants should be protected against blast of hand grenade HE36 or equivalent directly under the vehicle (d)Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e)Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapne protection for fuel tank. (g) Rediator. Matching Bullet proof protection as meeticand in an article and sides.	
Crew. Load carrying capacity Range of Operation Speed Protection level to be provided to the	The vehicle should have adequate space for internal fitment and storage. Driver + 4 fully equipped soldiers. Note Seats to be folding type to enable carriage of stores if required. Seat belt to be catered for troops, driver and co-drivers. Minimum 500 Kgs. (a)In plains - 300 to 350 kms. (b)In mountain - 250 to 300 kms. (a)On Road: Not less than 80 kmph with full load. (b)X Country: Not less than 40 kmph with full load. (a)Top. With stand direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62x3 mm at a distance of 10M at an angle of 45°. (b)All Sides. With stand, direct hit of 7.62x51mm Ball, 5.56x45 mm and 7.62 x 39 mm at a distance of 10M at 90 degree angle of attack. (c)Bottom Under Carriage. Passengers / occupants should be protected against blast of hand grenade HE36 or equivalent directly under the vehicle (d)Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e)Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapne protection for fuel tank. (g) Rediator, Matching Bullet proof protection as metrioned in the proof protection as met	
Crew. Load carrying capacity Range of Operation Speed Protection level to be provided to the	Driver + 4 fully equipped soldiers. Note Seats to be folding type to enable carriage of stores if required. Seat belt to be catered for troops, driver and co-drivers. Minimum 500 Kgs. (a)In plains - 300 to 350 kms. (b)In mountain - 250 to 300 kms. (a)On Road: Not less than 80 kmph with full load. (b)X Country: Not less than 40 kmph with full load. (a)Top. With stand direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62x3 mm at a distance of 10M at an angle of 45°. (b)All Sides. With stand, direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62 x 39 mm at a distance of 10M at 90 degree angle of attack. (c)Bottom Under Carriage. Passengers / occupants should be protected against blast of hand grenade HE36 or equivalent directly under the vehicle. (d)Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e)Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapne protection for fuel tank. (g) Rediator, Matching Bullet proof protection as mertioned in the side of the shade	
Capacity Range of Operation Speed Protection level to be provided to the	carriage of stores if required. Seat belt to be catered for troops, driver and co-drivers. Minimum 500 Kgs. (a) In plains (b) In mountain (a) On Road: Not less than 80 kmph with full load. (b) X Country: Not less than 40 kmph with full load. (a) Top. With stand direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62x3 mm at a distance of 10M at an angle of 45°. (b) All Sides. With stand, direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62 x 39 mm at a distance of 10M at 90 degree angle of attack. (c) Bottom Under Carriage. Passengers / occupants should be protected against blast of hand grenade HE36 or equivalent directly under the vehicle. (d) Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e) Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapne protection for fuel tank. (g) Rediator. Matching Bullet proof protection as meeticaged in the proof protection as m	
Capacity Range of Operation Speed Protection level to be provided to the	Co-drivers. Minimum 500 Kgs. (a) In plains (b) In mountain (a) On Road: Not less than 80 kmph with full load. (b) X Country: Not less than 40 kmph with full load. (a) Top. With stand direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62x3 mm at a distance of 10M at an angle of 45°. (b) All Sides. With stand, direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62 x 39 mm at a distance of 10M at 90 degree angle of attack. (c) Bottom Under Carriage. Passengers / occupants should be protected against blast of hand grenade HE36 or equivalent directly under the vehicle (d) Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e) Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank, Similar protection levels as for sides and under carriage i.e. shrapne protection for fuel tank. (g) Rediator, Matching Bullet proof protection as meetioned in an article and articles.	
Capacity Range of Operation Speed Protection level to be provided to the	Minimum 500 Kgs. (a) In plains (b) In mountain - 250 to 300 kms. (a) On Road: Not less than 80 kmph with full load. (b) X Country: Not less than 40 kmph with full load. (a) Top. With stand direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62x3 mm at a distance of 10M at an angle of 45°. (b) All Sides. With stand, direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62 x 39 mm at a distance of 10M at 90 degree angle of attack. (c) Bottom Under Carriage. Passengers / occupants should be protected against blast of hand grenade HE36 or equivalent directly under the vehicle (d) Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e) Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank, Similar protection levels as for sides and under carriage i.e. shrapne protection for fuel tank. (g) Rediator, Matching Bullet proof protection as mentioned in the carriage i.e. and the carriage i.e. shrapne protection for fuel tank.	
Capacity Range of Operation Speed Protection level to be provided to the	(a) In plains (b) In mountain (a) On Road: Not less than 80 kmph with full load. (b) X Country: Not less than 40 kmph with full load. (a) Top. With stand direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62x3 mm at a distance of 10M at an angle of 45°. (b) All Sides. With stand, direct hit of 7.62x51mm Ball, 5.56x45 mm an 7.62 x 39 mm at a distance of 10M at 90 degree angle of attack. (c) Bottom Under Carriage. Passengers / occupants should be protected against blast of hand grenade HE36 or equivalent directly under the vehicle. (d) Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e) Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapne protection for fuel tank. (g) Rediator. Matching Bullet proof protection as mentioned in the carriage i.e. and the carriage i.e. shrapne protection for fuel tank.	
Operation Speed Protection level to be provided to the	(a) On Road: Not less than 80 kmph with full load. (b) X Country: Not less than 40 kmph with full load. (a) Top. With stand direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62x3 mm at a distance of 10M at an angle of 45°. (b) All Sides. With stand, direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62 x 39 mm at a distance of 10M at 90 degree angle of attack. (c) Bottom Under Carriage. Passengers / occupants should be protected against blast of hand grenade HE36 or equivalent directly under the vehicle. (d) Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e) Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapned protection for fuel tank. (g) Rediator. Matching Bullet proof protection as meetioned in the 700 meeting as meetinged in the 700 meeting as meeti	
Speed Protection level to be provided to the	(a) On Road: Not less than 80 kmph with full load. (b) X Country: Not less than 40 kmph with full load. (a) Top. With stand direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62x3 mm at a distance of 10M at an angle of 45°. (b) All Sides. With stand, direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62 x 39 mm at a distance of 10M at 90 degree angle of attack. (c) Bottom Under Carriage. Passengers / occupants should be protected against blast of hand grenade HE36 or equivalent directly under the vehicle. (d) Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e) Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapned protection for fuel tank. (g) Rediator. Matching Bullet proof protection as meetioned in the 700 meeting as meetinged in the 700 meeting as meeti	
Protection level to be provided to the	(a)On Road: Not less than 80 kmph with full load. (b)X Country: Not less than 40 kmph with full load. (a)Top. With stand direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62x3 mm at a distance of 10M at an angle of 45°. (b)All Sides. With stand, direct hit of 7.62x51mm Ball, 5.56x45 mm an 7.62 x 39 mm at a distance of 10M at 90 degree angle of attack. (c)Bottom Under Carriage. Passengers / occupants should be protected against blast of hand grenade HE36 or equivalent directly under the vehicle. (d)Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e)Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapne protection for fuel tank. (g) Rediator. Matching Bullet proof protection as mentioned in an angle.	
be provided to the	(b)X Country: Not less than 40 kmph with full load. (a)Top. With stand direct hit of 7.62x51 mm Ball, 5.56x45 mm and 7.62x3 mm at a distance of 10M at an angle of 45°. (b)All Sides. With stand, direct hit of 7.62x51 mm Ball, 5.56x45 mm an 7.62 x 39 mm at a distance of 10M at 90 degree angle of attack. (c)Bottom Under Carriage. Passengers / occupants should be protected against blast of hand grenade HE36 or equivalent directly under the vehicle. (d)Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e)Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapne protection for fuel tank. (g) Rediator. Matching Bullet proof protection as meetioned in the 700 minimum 700 mm.	
be provided to the	mm at a distance of 10M at an angle of 45°. (b) All Sides. With stand, direct hit of 7.62x51mm Ball, 5.56x45 mm an 7.62 x 39 mm at a distance of 10M at 90 degree angle of attack. (c) Bottom Under Carriage. Passengers / occupants should be protected against blast of hand grenade HE36 or equivalent directly under the vehicle. (d) Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e) Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapne protection for fuel tank. (g) Rediator. Matching Bullet proof protection as meetioned in new 700.	
be provided to the	(b) All Sides. With stand, direct hit of 7.62x51mm Ball, 5.56x45 mm an 7.62 x 39 mm at a distance of 10M at 90 degree angle of attack. (c) Bottom Under Carriage. Passengers / occupants should be protected against blast of hand grenade HE36 or equivalent directly under the vehicle. (d) Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e) Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapned protection for fuel tank. (g) Rediator. Matching Bullet proof protection as meetioned in new 76%.	
	(b) All Sides. With stand, direct hit of 7.62x51mm Ball, 5.56x45 mm an 7.62 x 39 mm at a distance of 10M at 90 degree angle of attack. (c) Bottom Under Carriage. Passengers / occupants should be protected against blast of hand grenade HE36 or equivalent directly under the vehicle. (d) Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e) Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapned protection for fuel tank. (g) Rediator. Matching Bullet proof protection as meetioned in new 76%.	
	(c) Bottom Under Carriage. Passengers / occupants should be protected against blast of hand grenade HE36 or equivalent directly under the vehicle. (d) Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e) Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapne protection for fuel tank. (g) Rediator. Matching Bullet proof protection as meatinged in new 300.	
	against blast of hand grenade HE36 or equivalent directly under the vehicle. (d) Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e) Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapne protection for fuel tank. (g) Rediator. Matching Bullet proof protection as mentioned in new 700.	
	(d) Wheel. Tyres with run flat system be provided which should have run flat capability of minimum 10 kms. (e) Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapne protection for fuel tank. (g) Rediator. Matching Bullet proof protection as meetioned in non-2013.	
	flat capability of minimum 10 kms. (e) Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapne protection for fuel tank. (g) Rediator. Matching Bullet proof protection as meetioned in a red.	
	(e) Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapne protection for fuel tank. (g) Rediator. Matching Bullet proof protection as mentioned in new 300.	
	(e) Glass, Windshield and Side Glass. Same as per sides. (f) Fuel Tank. Similar protection levels as for sides and under carriage i.e. shrapne protection for fuel tank. (g) Rediator. Matching Bullet proof protection as mentioned in page 30.	
	protection for fuel tank. (g) Rediator. Matching Bullet proof protection as mentioned in normal action.	
	(g) Rediator. Matching Bullet proof protection as mentioned in and and	
	(g) Rediator, Matching Bullet proof protection as mentioned in and and a	
	catared for	
	Maintenance Free Batteries.	
re Extinguisher	Min. 2 Kg pressure ABC type. Fire suppression agents be provided 6.	
Constitution of the Consti	in a distribution of the second of the secon	
ir Conditioner	Air conditioner to meet the following requirements:-	
	(a) Final inside temperature: $25 \pm 5 \circ C$	
į	(b) Relative humidity of cooled air 30 to 75 %	
	(c) Maximum air speed; 0.5 m/s.	
	Ratio should not be less than 24kw/Ton.	
	Front suspension to be independent.	
ering	Power Steering to be provided.	
rning Radius	Turning radius to be not more than 7 mtrs	
ound Clearance	Min. 220mm and water fording capability without any preparation of the	
	500111111.	
erating 1	Keeping the employability from -20° to +50° C.	
uperature		
	Air and Noise pollution to conform to CPCB/CMVR norms.	
chain of the	a) Width - Not more than 2 mire	
icle "	E 14 AL	
1 1	1101 Hillie man a vinten	
	Not more than 4.5 mtrs c)Height It should be max 2 mtrs. Nan. 3500 Kg.	
of the second se	rning Radius ound Clearance erating sperature ution ension of the	

3/10/10

Z=3:12.v

W 231215

ja si sii si

	Weight		
20	Inspecting Authority	The user may formulate his own testing procedure or adopt the following DGQA/MOD Procedure:	
		(a)AHSP responsibilities for different stages of inspection of bullet proof	
		vehicle are as under:-	
	İ	(i) Automotive vehicle portion after bullet proofing:-	
		Inspecting Authority – CQA (V) Ahmednagar	
		Inspecting Officer-Concerned SQAO	
		(ii)Armoured Steel	
		Inspecting Authority- CQA (Metals) Ichapur	
	•	Inspecting Officer-Concerned SQAO	
		(iii)Kevlar	
		Inspecting Authority - CQA (T & C) Kanpur	
	-	Inspecting Officer-Concerned SQAO	
		(iv)Bullet Proof Glass	
		Inspecting Authority - CQA (Metals) Ichapur or TBRL Chandigarh	
	 -	Inspecting Officer-TBRL Chandigarh	
		(v)Proof/Firing Trials	
		Inspecting Authority - CQA (Small Arms) Ichapur	
		Inspecting Officer-Concerned SQAO	
		(vi)Air Conditioner	
		Inspecting Authority – CQA (EE) Pune	
21	Oparation	Inspecting Officer-Concerned SQAO	
	Operation and	Should be simple and easy.	
17	Maintenance		
12	Complete literature, illustrated diagrams, list of spares, special tools etc and operating instructions		
[[for the operation and	for the operation and maintenance of the vehicle and accessories should be provided.	
13 j	All reports for the materials used be provided by the firms from NABL accredited labs. The B.P. Vehicle after armouring must be CMVR certified.		
24	The B.P. Vehicle after armo	turing must be CMVR certified.	

23/12/15

Z=3-12.4

23.12.15