103

ज्ञापांक **1254/399368**/आपूरि

पुलिस महानिदेशक का कार्यालय, बिहार, पटना

पटना,दिनांक-- 04/12/18

सेवा में,

निदेशक, सूचना एवं जनसम्पर्क विभाग, बिहार, पटना।

विषय- पुनर्निविदा आमंत्रण सूचना सं0-19/2018-19 के प्रकाशन के संबंध में।

निदेशानुसार उपर्युक्त विषय के सबंध में पुनर्निविदा आमंत्रण सूचना सं0—19/2018—19 की प्रतियाँ भेजते हुए अनुरोध है कि इसे राज्य एवं राज्य से बाहर के प्रमुख समाचार पत्रों में (अंग्रेजी एवं हिन्दी) के अगले दो संस्करणों में प्रकाशित कराने की कृपा की जाय साथ ही पी03ार0डी0 वेबसाईट पर भी प्रसारित करने की कृपा की जाय।

इस निविदा आमंत्रण सूचना का प्रकाशन किन-किन समाचार पत्रों में किया गया इसकी सूचना देने की कृपा की जाय।

अनु0-यथोपरि।

पुलिस महानिरीक्षक के सहायक (क्यू०), बिहार, पटना

प्रतिलिपि:--

- 1. आई0टी0 मैनेजर, पुलिस महानिदेशक का कार्यालय, बिहार, पटना को कृपया सूचनार्थ। कृपया इसे आज ही वेबसाइट पर अपलोड किया जाय। साथ ही Indian Trade Journal, Kolkata के अंक में प्रकाशन हेतु Government of India, the Controller of Publications, Civil Lines, Delhi: 110 054,(Tel No. 011-23812527, FAX: 011-23817846), Email Idsk.mondal.dgcis@nic.in के पतेपर भी अनिवार्य रूप से भेजा जाय।
- 2. Government of India, the Controller of Publications, Civil Lines, Delhi: 110 054,(Tel No. 011-23812527, FAX: 011-23817846), Email Idsk.mondal.dgcis@nic.in को कृपया सूचनार्थ एवं आवश्यक क्रियार्थ प्रेषित। अनुरोध है कि उक्त निविदा का प्रकाशन Indian Trade Journal, Kolkata के अंक में करने की कृपा की जाय।

पुलिस महानिरीक्षक के सहायक (क्यू०), बिहार, पटना

<u>Police Headquarters, Bihar, Patna</u> <u>Notice Inviting Re-Tender No.-19/2018-19</u>

- 1. Name of the Department: Office of Director General of Police, Bihar, Patna.
- 2. Date & Time for Pre-Bid Meeting:

17/12/2018 At 11:30 AM

- 3. Last date & time for the acceptance of the re-tender: 09/01/2019, Till 02:00 PM
- 4. Date & time fixed for the opening of the re-tender:

09/01/2019, At 04:00 PM

- 5. Place fixed for receiving & opening the tender: Office of Director General of Police, Bihar, Patna.
- 6. Details of Job:

S.N.	Item name	Quantity
1	Server (AS + DB + IMS Proxy Sever)	03
2	PCs for alarms with RHEL 6	01
3	PCs for monitoring, provisioning and intercept administration and system administration with Windows 8.1	06
4	Router, Firewall etc, as per specifications attached as Annexure A	01
5	OS: RHEL server version 6.6 software	03
6	DB: My SQL Enterprise server software perpetual license	01
7	RJ - 45 Cat 6E cables, 3 Mtrs	15
8	19" rack with KVM, rack optimized mouse, keyboard & Monitor	01

Specifications and other terms & conditions of the tender may be obtained in person from this office or may be downloaded from the website www.prdbihar.gov.ir or www.biharpolice.bih.nic.in.

AIG (Q) Bihar, Patna

Terms & Conditions of Re-Tender No.-19/2018-19



- 1 The tender should be submitted in two parts: (i) Technical Bid and (ii) Financial Bid, duly scaled in two separate envelopes super-scribed as "Technical Bid" and "Financial Bid".
- 2. All relevant papers/ E.M.D./certificates/specifications etc. of items should be enclosed in the Technical Bid.
- 3. The rates of the items shall be quoted in the Financial Bid only.
- 4. All charges like IGST/CGST/SGST etc. shall be clearly mentioned in the Financial Bid and the net rate (in figures and words) including all taxes and duties must also be quoted. Vague offers like indicating taxes "as applicable" will not be accepted.
- 5. The rates of the items shall be quoted in the Financial Bid in two parts:
 (i) With AMC (Annual Maintenance Contract) and (ii) Without AMC
- 6. There should be no cutting, over writing or correction on the rates.
- 7. The technical and financial bids for each item should be submitted separately in separate envelopes. The technical and financial bids for more than one items submitted together in the same envelope shall not be accepted.
- 8. If the financial bid is submitted in the same envelope containing the technical bid then also it shall be summarily rejected.
- 9. The technical and financial bids should be put in two separate sealed envelopes and the envelopes should be marked Re-Tender No-19/2018-19 (Technical Bid) and Re-Tender No-19/2018-19 (Financial Bid) along with the name and address of the firm. The sealed envelopes containing the technical and the financial bids should be sent in another sealed envelope which should be marked as Re-Tender No-19/2018-19. This envelope should not bear the name and address of the firm.
- 10. Income Tax Returns of last three years, a photocopy of GST registration number of the participating firm and turn-over of any two of the previous three financial years should be submitted with the technical bid. It should be specifically mentioned whether IT return has been filed manually or electronically.
- 11. The turnover of the firm for the last reported financial year should be at least equal to the amount of the supply order which is being issued. A copy of the profit and loss Account of the firm for any two of the previous three financial years, certified by a Chartered Accountant should be submitted along with the tender. If the tenderer is authorized dealer or authorized supplier of manufacturing firm, then the certified details of the turnover of authorizing firm may be accepted. Tender specific authorization from the OEM must be submitted, but in certain cases where authorization from OEM is not required, the Technical-cum-User committee (T.U.C.) shall decide about exemption (if any) on a case-by-case basis; citing appropriate reasons for the same.
- 12. If there is some discount in the price of any item, it should be deducted from price itself and such discounts should not be quoted separately.
- 13. If the product is available on DGS & D rate contract, then a copy of the contract must be attached and pricing be done including all taxes.
- 14. A copy of the test report for the product issued by any established and recognized private Laboratory or by agency accredited by the Government should be attached with the technical bid. However if required, the Technical-cum-User committee (T.U.C.) can take decision regarding exemptions/relaxations (if any), citing appropriate reasons.
- 15. In case of Bullet Proof/Bullet Resistant items, test report of TBRL or any Government Approved/Recognized Laboratory is compulsory.

- 1100
- 16. Firms participating in this tender shall also submit duly sworn affidavit to the effect that "this firm has not been black listed/debarred by any Government or Semi Government or Private Agency and no sister concern of this firm is participating in this tender."
- 17. Firms participating in this tender shall also submit the self attested list of users of its equipments.
- 18. All items shall be received at Central Clothing Store, Patna; therefore price should be quoted FOR Central Clothing Store, Phulwari Sharif, Patna.
- 19. Firms will have to deposit a sum of Rs.50,000/- (Fifty Thousand) only as an earnest money deposit in the form of Bank Draft duly pledged in favor of the undersigned along with the quotations. The small scale units located in Bihar shall not be liable to deposit earnest money. Exemption from submitting E.M.D. will also be available to those who are registered with the Central Purchase Organization/State Purchase Organization and National Small Industries Corporation (NSIC).
- 20. Technical Bids will be opened on scheduled date and time in the office chamber of Police Headquarter. Representatives of the firms competing in the tender may remain present at the time of opening of the technical bid.
- 21. The technical bids will be opened first and placed before the Technical Committee of the Police Headquarters, Bihar. If the technical bids are found satisfactory as per tender conditions, it will be put before Central Purchase Committee of the Police Headquarters, Bihar. The firms may be required to participate in the demonstrations of the quoted product and discussions with this committee.
- 22. Any paper/document will not be accepted after opening the tender.
- 23. Successful firm will have to enter into an agreement after depositing a sum of 5% of the total value of the order as security money in the form of Bank Guarantee duly pledged in favor of undersigned.
- 24. The firm will be required to provide satisfactory after-sales service after the delivery of the product.
- 25. The firm will be required to supply all the items within the stipulated time frame as mentioned in the purchase order.
- 26. Payment for the delivered items will be made only after the acceptance report of the Inspection Committee of the Police Headquarters, Bihar.
- 27. The firm whose quotation is approved by the Central Purchase Committee of the Police Headquarters, Bihar, shall be invited to enter into an agreement with the undersigned.
- 28. It is expected to submit the duly filled chart attached herewith, along with the technical bid if not the tender shall be summarily rejected.
- 29. Indexing of the requisite documents must be done and submitted along with the technical bid.
- 30. Hands on training for 3 weeks of the equipment must be imparted to the user group by the firm after successful installation.
- 31. Director General of Police Bihar, Patna reserves the right to reject any or all the quotations partially or fully, without assigning any reason thereof.
- 32. The Quantity indicated may increase or decrease at the time of issuing purchase order.
- 33. The bids must be include the data sheet of individual item.

A I G (Q) Bihar, Police.

1.Specification of Servers

S. No. 1	Parameter Processor No of Processors	Specifications Intel® Xeam® processor E5-2690 v3 or higher
3.	PCI Slots	128 GR using 8x16GB 16GB RDIMM, DDR4-2133/MTb, Doal Park x-1 Data Width (LRDIMMs also acceptable) Minimum 1 nos. of PCI-Express Gen3 Slot shall be available for future expansion (After taking into account all the mandatury and optional hardware mentioned in this document)
5.	Interface Ports	a) Serial port -1; b) Mouse -1; c) Keyboard -1; d) VGA Graphics -1; e) USB 3.0 or above -4; f) RJ45 Network ports - 4 +1 (for Remote Management) (In case Mouse and Keyboard are USB based then additional USB ports to be given. Similarly, for serial port converted from USB additional USB port shall be provided along with USB to Sec. al converter.)
6.	Hard Disk Drive	To be supplied with 6 x 900GB (or higher capacity) 12G SAS Enterprise HDD in RAID6.
7.	Bnys	Should support minimum 8 nos. of SAS Drives
ď	RAID Controller	12 Gbps or higher throughput HW RAID Controller supporting RAID 0/1/1+0/5/6 with minimum 1 GB of Flash-backed write cache

/		.17:
; 9	FC HBA	2 x Single Port Qlogic 8Ghps FC Host Bus Adapter
10.	Optical Drive (internal)	DVD-RW Drive (or DVD/CD Compatible Blu-Ray Desc Drive)
ļii L	Graphics	Integrated on-board graphics with support for 16 Milhon color, resolution of 1280 x 1024
12	Greatur	1 nos of Guabit Ethernet ports full duplex. The network ports should also provide the following functionalities for all supported OS. • Ethernet Bonding, Failover and load balancing. • Wake on LAN, • Pre-Boot Execution Environment (PXE), • Multiple VI AN tagging.
13.	Redundant Power Supplies	Auto-negotiation for 10/100/1000 Mbps Redundant Hot Plug Power Supplies (230 VAC). The power supplies shall be either 80 Plus platinum certified or better
14	Redundant	Redundant Hot Plug fans
i	cooling Fans	
15.	Form Factor	Rack mountable with rack mount kit and rails (preferably 211 or less)
ÎĞ.	OS Support	The quoted server should support the following Operating Systems a) RHEL 6 and above; b) VMware vSphere TM 5.0 and above
17.	Backup drive	LTO-6 tape drive (preferably internal) with six media and one cleaning cartridge
		*in case external tape drive is quoted additional controller and rack mounting accessories shall be provided
18	Remote Manageability	 a) It shall be possible to manage the server hardware and software components remotely. b) The server hardware shall be manageable even when it is shutdown or crashed.
		c) It shall be possible to power on/off and boot the system remotely: d) It shall have the following features: • real time power reading;
: !	İ	POST and failure sequence replay;
		• Event log;
	!	Browser and CLI support;
		Secure Socket Layer;
	:i	Secure Shell.

	rver inagement	OEM software for management of Servera must be included as standard. It should integrate with any SMMP based industry standard. Network Management Software. (The SMMP MIBs for all the bardware and software components shall be provided in a DVD media). Should provide Fault management and automatic event handling through e-mail, SMS, Should provide Role based secured remote management using Secure Sockets Layer (SSL) and Secure Shall (SSH) to encrypt management communications. Should provide Pre-failure warning for CPU, Memory,
20. W	arranty	and HDD. Should have local LED/LCD based diagnostic panel for easy fault identification. The entire hardware and software shall carry a comprehensive onsite warranty of 3 years from the date of commissioning

2. PCs for monitoring, provisioning and intercept administration and system

We need 6 node for monitoring in STF

Į

۲

Specification of Six desktop with UPS backup

S. No.	Parameter	Details
1	CPU/Speed	Intel 6th Gen. Core i7 6700 or higher
2	RAM	8GB (2 x 4 GB) 1600 Mhz DDR3/DDR4 NON ECC SDRAM upgradable to 16 GB or more. Minimum 4 memory slots
:1	Storage	2 x 1 TB 7200 rpm SATA III HDD or higher DVD-RW Drive
ı	Video Controller	Integrated
Fg.	Monitor	21.5" TFT Flat Panel Display LED backlit (Full HI))
fi .	Keyboard 	Multimedia/Internet Keyboard and Optical Mouse from desktop
7	Audio	Integrated, External Stereo Speakers and noise cancellation typ
H	Network interface	2 x 10/100/1000 Mbps Ethernet Network Card, Auto sensing.
4	Bus Slots	One x16 PCI Express slot
II)	Ports	Minimum 6 USB 2.0/3.0 ports 1 RJ-15 1 VGA
	Manse	2 Line in (stereo/microphone) 2 Line out (headphone/speaker) Optical Scroll (3 button) Mouse with mouse pad
2 !	Power Supply	220-210 VAC, 50 Hz With Indian Power cables

is •	Drivers Accessorie	Required drivers and cables to be provided
-	0.8	(a) Genuine Microsoft 64 bit Windows 8.1 Professional with License and Media. (Restore CD's not acceptable. Required Driver CD's to be provided).
13 Warranty		the Autivirus with three years' aubscription
	(a) 3 years Comprehensive onsite warranty support for Hardware and OS from the date of Installation/Acceptance (b) Vendor should provide OEM warranty card mandatority (c) The equipment shall be supported for at least 5 years from	
16	Pest Sales Support	the date of neceptance Principal/Supplier should have a full-fledged service center at the city of installation
1:	Installation	Installation/Creation of Partition, OS Installation and enabling
18	Cables, Drivers connectors and accessories	All the necessary cables, drivers, connectors and necessories if any should be provided.

(3). For DB: My SQL Enterprise server software perpetual license

(4). Specification for 19" Rack

21

Ų:

ic

Ü

ত

	51.	Specifications
_	1	DIMENSIONS: -12U 800mm (W) X 1200mm (D)
<u>.</u>	-	Color: Powder coated Black
-	i i	At least two (2) rear vertically mounted PDUs with a total of 24 nos. of 6A/16A, 230V, C13 sockets. The imputs to the PDUs shall be provided using NEMA connectors. Two sets of single phases 32A NEMA connectors (each set inclusive of both male and female parts) along with 2 nos. of 32A MCBs and mounting boxes' shall be provided. 15-meter-long FRLS power cables with each wire having 4 mm² cross sectional area shall be provided for input to each PDU. The electrical cabling from the UPS output point evaluable at the site to the NEMA connector BOX near the rack shall have to be carried out by the bidder thing 1 mm² fRLS cable and appropriate cap-on-casing or conduit depending on the site suitability. All ables, sockets and circuit breakers shall be ISI/UL certified.
1,	110	lote: Compatible Power Cords should be provided for all Equipment Supplies. op mounted fan Tray with a fans (should not consume mounting slots (out of 42 U) or sockets in the DU)
٢.	- 1	fued tray
G,	1	sliding 20 drawer
7	*	* * ***********************************
<u>s.</u>	1	theels with locks U sliding rack optimized Keyboard, mouse, monitor with KVM to connect 6 servers and the networking tuipment

	ver
٠.	gertorated metal front door (single) and back doors (double) with door knobs at the outside of the there shall be two LED L.
3° { 1	there shall be two LCD lamps inside the cost.
-	there shall be two tasts and and had been supposed and the angel and the most supposed and the supposed and
	TO SELECT SERVICE SERV
Ì	turn on only when the front door and the back doors are opened. The purpose is to provide visibility to
	the front and back sides of the equipment middle the rack. Rear vertical cable managers
١	Rear vertical cable managers equipment mide the rack.
į,	Weight adu batel
ί1.	A STATE OF THE PARTY OF THE PAR
•	Mountury Hardware
15	
10	A Packet consisting of 100 nos of reusable Velcro tle wraps
17	RE-15 Cat 6L patch cords, factory crimped with boot for protection, UL/ETL Certified, length, length: 3
	Motors

(5). Specification for for Secure Service router

	Specifications
3.No.	Specifications such as
Λ.	Performance Requirement Wire-speed performance equivalent to 45Mbps or higher for concurrent services such as Routing and Firewall, IPS, VPN, Encryption/Decryption.
1.	Wire-speed performance equivalent to 401/10ps of 118
2.	Wire-speed performance equivalent to 40Mpps of the Routing and Firewall, IPS, VPN, Encryption/Decryption. Routing and Firewall, IPS, VPN, Encryption/Decryption. Active/Active and Active/Standby support for all services and stateful failover of runtime sessions using integrated or dedicated Stateful Firewall. Incase if firewall is runtime sessions using integrated or dedicated Stateful Firewall. Incase if firewall is dedicated module or chassis it should support transparent mode to avoid the creation of the result is not work in-between.
	I fillifillife accounts manny
	dedicated module or cansas translation and selection and selection dedicated module or cansas translation and selection and sele
	additional Ballesia and Swilliaghit SFP (SX & LX one case)
3.	Ports should be usable in any combination) Ports should be usable in any combination)
	Ports should be usable in any combination, • 16x10/100/1000 Mbps L3 Switched Ports at wire speed. • 16x10/100/1000 Mbps L3 Switched Ports at wire speed. Hardware based encryption and VPN Support for 3DES, and AES 256, VPN tunnels.
	• 16x10/100/1000 map
4.	Intrusion Prevention as well as other essential security features.
5.	Intrusion Prevention as well as other essential
1	Pauling & Multicasting
B. 6.	Routing & Multicasting 1Pv4 and 1Pv6 support, including 1Pv4-IPv6 tunnels 1Pv4 and 1Pv6 support, including 1Pv6, OSPFv2 and v3, BGP4/4+
<u>-6:</u> -	IPv4 and IPv6 support, including IPv4-IPv6 tunners IPv4 and IPv6 support, including IPv4-IPv6 tunners Static routing, RIPv1/2, RIPng for IPv6, OSPFv2 and v3, BGP4/4+
7. 8.	Policy-based routing
9.	"The Stability VRRP redundant forter connections
10.	High availability. Victor IPv6 IGMPv1/2/3 for IPv4; MLDv1/2 for IPv6
<u> </u>	1(iw)(V)(124) 101 (1 V 4) 1124
12.	PiM-SM for IPv4/v6
C.	LAN Features
13.	10/100/1000 Base-TX
14.	10/100/1000 Base-1X IEEE 802.1x port authentication, MAC based authentication
15.	TEEE 802.1p
16.	TEEE 802.1Q
17.	TEEE 802.3ad LACP
18.	TEEE 802.1s MSTP
19.	VLAN Registration Protocols for dynamic VLANs
20.	Port mirroring
21.	Jumbo frames
-"n.	WAN Features

7	······································	
22.21.44 25. E. 26.5	Serial V.35 - Specifications	
22.	Point-to-Point Protocol (PPP), including PPP over Ethernet (PPPoE) Multilink PPP (MLPPP)	,
23.	Point-to-Point Protocol (PPP), includios ppp	
1-24.	Abdulant DDD as a second of the second (PPPoE)	
25.	Multilink PPP (MI, PPP)	
Fi	Quality of Service/Traffic Management WRED, DiffServ, bandwalt	
26.	WRED. DiffServ. bandwidth gunrantee/sharing. flow monitoring, traffic policing Slevel Princite Class Based Queuing - Per IP address/subjects, poets, DSCP and ToS	
27.		
	I DITALLY A CALLA LALL LALLA LALLA LA LA LA CALLA CALL	
28.	VLAN Classification (port and MAC based)	
Tr.		
29.	Scattelul Packet Inspection and failover Firewall	
30	Routed or transparent mode of operation	
-:11	Multiple zone support (including Corporate, Internet, DMZ)	
一:12	Acress Control Lists (ACL)	
33.	NAT, including policy-based NAT/PAT	
-31.	Multiple Distributed Developed To and To State L Beautions	٠
35.	Multiple Distributed Denial of Service (DDoS) Attack Preventions IPSec. L2TP, PPTP	. 1
36.	IPS Into and All in the Interest of the Intere	4
	viruses. Signature updation/distribution should be possible through centrally placed in-	à
	house management server.	1
Γ G.	VPN	1
37.	Integrated hardware for encryption and VPN acceleration	7
38.	IPSec VPN with Stateful failover, Group VPN Based on RFC 6407, GDOI	ž
39.	BDES, AES, SHA1, SHA-256	4
40.	VI'N Client support	2
Н.		Ġ
41.	Management & Service provisioning Management: Telnet, SSHv2, SFTP, PAP, CHAP, SNMPv2, SNMP v3, DHCP, DNS Management: Telnet, SSHv2, SFTP, PAP, CHAP, SNMPv2, SNMP v3, DHCP, DNS	1
	Proxy. RADIUS, TACACS*, PKI functions and management of Keyl Con-	13
	certificates.	{ :
42	Monitoring: Syslog, statistics, RMON, alarm Diagnostics: BERT, loopback testing, trace route, packet capture	\ .
43	Diagnostics: Biski, loopback testing, trace roate, passes aspect	1
: <u>L</u> _	Reliability & Availability Redundant power supply (Internal) and variable-speed cooling fans.	1
44	Redundant power supply (morney and	1
, 45.	Hot swappable Modules International Power Safety & Energy efficiency certifications	1
<u>J.</u>	International Fower Salety & Bloody Street	1
<u>: 46.</u>	UL/CSA/IEC/EN 60950-1 Common Criteria EAL3 certification (ISO/IEC 15408) for the product or family	4
47.	Common Criteria EALS certification (100/100 104/00) for the product or family	1
		1

1,